(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 15 January 2004 (15.01.2004)

PCT

(10) International Publication Number WO 2004/005610 A1

(51) International Patent Classification7:

D21C 11/12

(21) International Application Number:

PCT/FI2002/000611

(22) International Filing Date:

4 July 2002 (04.07.2002)

(25) Filing Language:

Finnish

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): FOR-TUM OYJ [FI/FI]; Keilanniementie 1, FIN-02150 Espoo
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SUNDMAN, Kari
- [FI/FI]; Haulikuja 4, FIN-93100 Nummela (FI). RAIKO, Markku [FI/FI]; Rajalantie 223, FIN-05800 Hyvinkää (FI). REPKA, Mika [FI/FI]; Rautahatuntie 30, FIN-00920 Helsinki (FI). SUTINEN, Jari [FI/FI]; Örkkiniityntie 74 as 1, FIN-02920 Espoo (FI).
- X) Haavistontie 18, FI- 33960 Pirkkala (74) Agent: FORSSÉN & SALOMAA OY; Eerikinkatu 2, FIN-00100 Helsinki (FI).


- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR TREATMENT OF SPENT LIQUOR



(57) Abstract: Method for treatment of spent liquor at a pulp mill, in which method at least a part of the spent liquor flow (10) arriving from the evaporation plant is taken to a pyrolysis reactor (1), wherein it is pyrolysed at a temperature of 300-800°C in order to separate evaporable compounds (12) from coke (11) remaining in a solid state. The pyrolysis products (12), which are gases or liquids, may be used as fuel or they may be processed further. The coke (11) resulting from the pyrolysis is burnt in a soda recovery boiler (3) or in a gasification reactor (2) to regenerate cooking chemicals. The method is suitable for recovery of chemicals and energy both in sulphate and sulphite processes and also in cooking methods based on organic solvents.

